



ROUGH TERRAIN FORKLIFT TRUCK



Model	SYC-15	SYC-30
Rated load	1,500KG	3,000KG
Lift height	Standard: 3m Optional: 4m, 4.5m	Standard: 3m Optional: 4m, 4.5m
Fork length	1,220mm	1,220mm
Engine power	42KW	42KW
Tire	825-16	20.5/70-16
Drive	4X4	4x4
Gradeability	40°	40°
Weight	2,800KG	4,000KG
Dimensions	3,350*1,400*2,250mm	4,200*1,800*2,700mm

**SYC-35****SYC-35** (SHORT FRONT AXIS VERSION)

Model	SYC-35	SYC-35 (SHORT FRONT AXIS VERSION)
Rated load	3,500KG	3,500KG
Lift height	Standard: 3m	Standard: 3m
	Optional: 4/4.5/5/6m	Optional: 4/4.5/5/6m
Fork length	1,220mm	1,220mm
Engine power	42KW	42KW
Tire	23.5/70-16	23.5/70-16
Drive	4x4	4x4
Gradeability	40°	40°
Weight	4,200KG	4,200KG
Dimensions	4,200*1,800*2,700mm	3,800*1,850*2,300mm

SYC-35 (SHORT REAR AXIS VERSION)**SYC-35** (SHORT VERSION ROOF)

Model	SYC-35 (SHORT REAR AXIS VERSION)	SYC-35 (SHORT VERSION ROOF)
Rated load	3,500KG	3,500KG
Lift height	Standard: 3m	Standard: 3m
	Optional: 4/4.5/5/6m	Optional: 4/4.5/5/6m
Fork length	1,220mm	1,220mm
Engine power	42KW	42KW
Tire	23.5/70-16	23.5/70-16
Drive	4x4	4x4
Gradeability	40°	40°
Weight	4,200KG	4,200KG
Dimensions	3,600*1,850*2,150mm	3,800*1,850*2,300mm

SYC-35 (MID MOUNTED HINGE ROOF)**SYC-35** (MID MOUNTED HINGE CABIN)

Model	SYC-35 (MID MOUNTED HINGE ROOF)	SYC-35 (MID MOUNTED HINGE CABIN)
Rated load	3,500KG	3,500KG
Lift height	Standard: 3m	Standard: 3m
	Optional: 4/4.5/5/6m	Optional: 4/4.5/5/6m
Fork length	1,220mm	1,220mm
Engine power	42KW	42KW
Tire	23.5/70-16	23.5/70-16
Drive	4x4	4x4
Gradeability	40°	40°
Weight	4,200KG	4,200KG
Dimensions	3,600*1,850*2,150mm	3,600*1,850*2,150mm

SYC-35 (LOW TYPE)**SYC-35** (REAR WHEEL STEERING)

Model	SYC-35 (LOW TYPE)	SYC-35 (REAR WHEEL STEERING)
Rated load	3,500KG	3,500KG
Lift height	Standard: 3m	Standard: 3m
	Optional: 4/4.5/5/6m	Optional: 4/4.5/5/6m
Fork length	1,220mm	1,220mm
Engine power	42KW	42KW
Tire	12-16.5	23.5/70-16
Drive	4x4	4x4
Gradeability	40°	40°
Weight	4,200KG	4,500KG
Dimensions	4,100*1,850*2,200mm	3700*1,850*2,350mm

SYC-35 (INTEGRATED TYPE)**SYC-40**

Model	SYC-35 (INTEGRATED TYPE)	SYC-40
Rated load	3,500KG	4,000KG
Lift height	Standard: 3m	Standard: 4m
	Optional: 4/4.5/5/6m	Optional: 4/4.5/5/6/7m
Fork length	1,220mm	1,520mm
Engine power	36.8KW	65KW
Tire	20.5/70-16	16/70-20
Drive	4x4	4x4
Gradeability	40°	40°
Weight	5,600KG	5,000KG
Dimensions	2,980*1,550*2,250mm	4,400*1,850*2,800mm

SYC-50**SYC-50** (SHORT AXIS VERSION)

Model	SYC-50	SYC-50 (SHORT AXIS VERSION)
Rated load	5,000KG	5,000KG
Lift height	Standard: 4m	Standard: 4m
	Optional: 4/4.5/5/6/7m	Optional: 4/4.5/5/6/7m
Fork length	1,520mm	1,520mm
Engine power	76KW	76KW
Tire	16/70-24	16/70-24
Drive	4x4	4x4
Gradeability	40°	40°
Weight	5,500KG	5,500KG
Dimensions	4,500*1,900*2,850mm	4,500*1,900*2,850mm



Model	SYC-60	SYC-70
Rated load	6,000KG	7,000KG
Lift height	Standard: 4m	Standard: 4m
	Optional: 4/4.5/5/6/7m	Optional: 4/4.5/5/6/7m
Fork length	1,520mm	1,520mm
Engine power	76KW	80KW
Tire	12R22.5	12R22.5
Drive	4x4	4x4
Gradeability	40°	40°
Weight	6,200KG	6,500KG
Dimensions	4,600*2,200*2,850mm	4,500*2,500*3,000mm



Model	SYC-80	SYC-100
Rated load	8,000KG	10,000KG
Lift height	Standard: 4m	Standard: 4m
	Optional: 4/4.5/5/6/7m	Optional: 4/4.5/5/6/7m
Fork length	1,520mm	1,520mm
Engine power	110KW	76KW
Tire	17.5-254	12R22.5
Drive	4x4	4x4
Gradeability	40°	40°
Weight	10,500KG	1.2000KG
Dimensions	5,800*2,200*3,100mm	5,800*2,400*3,300mm

OPTION



Adjustable Distance Fork



Down Tilt Fork



Barrel Clamp



Cylinder Holding Clamp



Soft Clamp




Steel Tube Clamp



Triple Gantry



Ejector



Flat Bucket



Multifunction Bucket



Fork Arm



Ejector



Log Grapppler



Air Conditioner



Solid Tire



Agricultural Tire

MORE ANGLES





TELESCOPIC HANDLER —

ST625 Torque Converter



ST625 Hydrostatic



Model	ST625 Torque Converter	ST625 Hydrostatic
Maximum lift capacity	2500KG	2500KG
Lift capacity to full height	2000KG	2000KG
Lift capacity at full reach	800KG	800KG
Lift height	5900mm	5900mm
Reach at maximum lift height	450mm	450mm
Weight unload	4988KG	4988KG
Tyre	14–17.5	14–17.5
Overall height	2000mm	2000mm
Inside width of cab	800mm	800mm
Overall length to front carriage	3900mm	3900mm
Engine brand	YUNNEI/YN27GBZ	YUNNEI/YN27GBZ
Engine rate power	58KW	58KW
Pallet fork length	1220mm	1220mm
Hydraulic oil tank	115L	115L
Diesel tank	63L	63L
Drive type	4 wheel drive	4 wheel drive



Model	ST730	ST735
Maximum lift capacity	3000KG	3500KG
Lift height	7000mm	7000mm
Reach at maximum lift height	450mm	450mm
Maximum forward reach	3600mm	3600mm
Weight unload	7000KG	7200KG
Tyre	16/70-20	16/70-24
Outside turn radius (over tyre)	4250mm	4250mm
Overall height	2300mm	2450mm
Overall width (over tyres)	2150mm	2150mm
Inside width of cab	800mm	800mm
Front track	1750mm	1750mm
Wheelbase	2850mm	2850mm
Overall length to front tyres	4200mm	4200mm
Overall length to front carriage	4650mm	4650mm
Ground clearance	350mm	350mm
Engine brand	YUNNEI YN38GBZ	YUCHAI YCD4J22T-115
Engine rate power	76KW	85KW
Pallet fork length	1220mm	1220mm



Model	ST740	ST750
Maximum lift capacity	4000KG	5000KG
Lift height	7000mm	7000mm
Reach at maximum lift height	450mm	450mm
Maximum forward reach	4000mm	4000mm
Weight unload	7800KG	10000KG
Tyre	16/70-24 Semi-solid tires	400/80R24
Outside turn radius (over tyre)	4250mm	4250mm
Overall height	2300mm	2400mm
Overall width (over tyres)	2150mm	2200mm
Inside width of cab	800mm	800mm
Front track	1750mm	1750mm
Wheelbase	2850mm	2850mm
Overall length to front tyres	4200mm	4200mm
Ground clearance	350mm	350mm
Engine brand	YUCHAI YCD4J22T-115	YUCHAI YCD4J22T-125
Engine rate power	85KW	91KW
Pallet fork length	1220mm	/

ST1035



ST1440



Model	ST1035	ST1440
Maximum lift capacity	3500KG	3500KG
Lift height	10000mm	10000mm
Weight unload	8375KG	8375KG
Tyre	16/70-24 Semi-solid tires	16/70-24 Semi-solid tires
Outside turn radius (over tyres)	4250mm	4250mm
Overall height	2300mm	2300mm
Overall width (over tyres)	2150mm	2150mm
Inside width of cab	800mm	800mm
Overall length to front tyre	4600mm	4600mm
Front track	1750mm	1750mm
Wheelbase	2850mm	2850mm
Ground clearance	350mm	350mm
Engine brand	YUCHAI YCD4J22T-125	YUCHAI YCD4J22T-125
Engine rate power	91KW	91KW
Pallet fork length	1220mm	1220mm

ST1840



Model	ST1840
Maximum lift capacity	4000KG
Lift height	17550mm
Weight unload	13000kg
Tyre	16.9-24 vacuum tires
Outside turn radius (over tyres)	≤4500mm
Overall height	2550mm
Overall width (over tyres)	2430mm
Inside width of cab	1000mm
Overall length to front tyre	4600mm
Front track	1990mm
Wheelbase	3670mm
Ground clearance	420mm
Engine brand	YUCHAI YCD4J22T-125
Engine rate power	91KW
Pallet fork length	1220mm

COMMON ATTACHMENTS



Mixed Fodder Clip



Extended Boom With Winch



Snow Shovel



Basket Work Platform



Brick Clamp



Snow Thrower



Light-Duty Material Bucket



Multi-Functional Agricultural Loader Bucket



Construction Bucket



Cement Mixer Bucket



Single Hook



Forward-Sweeping Road Sweeper

SHIPPING

